


CORKE™ 36

FPD6638**

36" Ceiling Fan




18° Blade Pitch


Net Hanging Weight: 12.61 lbs

7' min

Floor



featuring KwikWire easy connection



Ceiling Bracket Width of the screw slot

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

DC125 x 15 motor is designed for optimal performance with this fan.

BLADE SET:

A set of three 17" composite blades is included.

CONTROL OPTIONS:

A WiFi receiver and TR360 hand-held remote control are included. Push button remote control with 6 fan speeds, fresh air, reverse, ON/OFF dimmer light levels, 5 CCT Select (correlated color temperature selection), fan/light timer, home away, safe exit and off button. Visit the Apple APP Store or Google Play Store to download the free fanSync WiFi APP and create your Fanimation fanSync account. Optional TW406 wall control is available — sold separately. Instructions is provided with each control.

LIGHTING OPTIONS:

One 24-watt 5 CCT LED included.
(2700K/3000K/3500K/4000K/5000K)

LOCATION USE:

Fan is rated for dry and damp locations.
This fan is for room up to 100 sq ft.

Available Finishes

BL	Black with Black Blades and Opal Frosted Glass
BLK	Black with KOA Blades and Opal Frosted Glass
BSMW	Brushed Satin Brass with Matte White Blades and Opal Frosted Glass
MW	Matte White with Matte White Blades and Opal Frosted Glass

Airflow / Energy Efficiency Info (120V)

Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High (6 th)	320	3499	136	0.38	26
Med (4 th)	212	2561	294	0.14	9
Low (1 th)	50	541	224	0.05	2

Energy Guide FTC

Power (W _{ave})	Total Air Delivery (CFM _{ave})	Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)
18	2112	5	118

Fan Velocity (FPM)

High Speed Velocity	Average Velocity
589	334

Lighting Information (120V)

Light Bulb	Lumens Amount	Delivered Lumens	Color Temp	CRI	Shade/ Glass type
24W CCT LED	2000	987/1003/1066/1099/1111	Warm White/Soft White/Bright White/Cool White/Daylight	90%	Opal Frosted