



Project / Job Name:

Location:

Fixture Type:

Notes:

S12126 - 4.5 Watt Mini LED; G8 Base; 3000K; Clear Finish; 120 Volt



GENERAL

Company	SATCO
EA Height	4.84
EA Width	0.73
EA Length	3.27
Candle Power	35.0
Lamp Filament	LED
Material	Ceramic / Polycarbonate (PC)
Fixture Type	Miniature
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 1.5KV
Total Harmonic Distortion	70%
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Additional Info	Housing Material: Ceramic; Lens Material: Polycarbonate (PC)
Amps	0.037A
Has Camera	No
IOT Enabled	No
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	40W

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	300
Color Temp	Soft White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	430L
Volts	120v
Watts	4.5W

PHYSICAL

Lamp Base	Bi Pin G8
Finish	Clear
Housing Color	White
ANSI Base	G8
Lamp Type	T6
MOD Lamps	0.73
MOL	1.81

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923121265
Case Cube	0.666
Case Height	12.13
Case Length	10.04
Case Quantity	48
Case UPC	10045923121262
Case Weight	4.37
Case Width	9.45
EA Cube	0.0067
EA Height	4.84
EA Length	3.27
EA Quantity	1
EA Weight	0.06
EA Width	0.73
Inner Cube	0.1342
Inner Height	5.63
Inner Length	8.86
Inner Quantity	12
Inner UPC	20045923121269
Inner Weight	0.83
Inner Width	4.65
Pack Type	Carded
Web Length	1.81
Web Width	0.73

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No