



Project / Job Name:

Location:

Fixture Type:

Notes:

S9952 - 15 Watt PLL LED; 2G11 Base; 2000 Lumens;
120-277 Volt; 3500K; Type B; Ballast Bypass



GENERAL

Company	SATCO
EA Height	0.69
EA Width	1.5
EA Length	16.8
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass / Thermo Plastic (PBT) Cap
Fixture Type	PL
Status	Active
Style	Utility
Total Harmonic Distortion	20% (+/-5%)
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	CCT Selectable Option: S18422
Amps	0.125-0.054A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	36W
Incandescent Equivalent	75W

ELECTRICAL

CCT (Kelvin Temp)	3500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	270
Color Temp	Neutral White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1900L
Volts	120V-277V
Watts	15W

PHYSICAL

Lamp Base	4-Pin
Finish	Frost
Housing Color	White
ANSI Base	2G11
Lamp Type	T5
MOD Lamps	0.68
MOL	16.5

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923099526
Case Cube	0.2115
Case Height	5.32
Case Length	17.44
Case Quantity	10
Case UPC	10045923099523
Case Weight	4.0
Case Width	3.94
EA Cube	0.0101
EA Height	0.69
EA Length	16.8
EA Quantity	1
EA Weight	0.4
EA Width	1.5
Pack Type	Box
Web Length	16.5
Web Width	0.68

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No