INTERVALS®

20QKL08B

Sonneman

Intervals® is an LED-integrated linear architectural lighting system that blends old-world elegance with new-world minimalism. Architecturally scaled, the suspended horizontal beams are supported from slender ceiling-mounted cables or stems. Short cylindrical glass shades are mounted at equidistance along the frame, providing bidirectional illumination. Intervals® is available in five configurations with Satin White or Satin Black finish options.

FINISHES

SATIN BLACK



DIMENSIONS / SPECS

Height: 11.5"
Width/Diameter: 96.25"
Length: 4"
Minimum Height: 14.25"
Maximum Height: 86.25"
Canopy/Backplate: 4.5"
Hanging Type: 6' Adjustable Cable
Product Weight: 18lb
Canopy/Backplate Shape: Round
Sloped Ceiling Compatible: Yes
Living Finish: No
Uplight Only: No

Shade 1: Glass & Acrylic
Shade 1 Finish: Clear
Shade 1 Top Width: 3"
Shade 1 Height: 4"
Shade 2: Aluminum
Shade 2 Finish: Satin Black
Shade 2 Top Width: 3"
Shade 2 Height: 0.75"

ELECTRICAL

Bulb 1
Bulb Included: N/A
Socket: Integrated LED
Bulb Type: LED
Max Wattage: 5
Bulb Quantity: 6
Dimmer Type: ELV, TRIAC, 0-10 VOLT
Gem Box Required (2"x3"): No
Dark Sky: No
Convertible: No
CRI: 90
Color Temp.: 3000k
Lumens: 6069
Title 24: No
Field Serviceable: No
Voltage: 120-277V
Initial Lumens: 8670
IP Rating: N/A

Bulb 2
Bulb Included: N/A
Socket: Integrated LED
Bulb: LED • 6 • 10 Watt Max
Voltage: 120-277V
UL Rating: cETL Damp

INTERVALS®

20QKL08B

Sonneman

SHIPPING

Carton 1: 0" x 0" x 0"
Carton 1 Weight: 0lb
Shipping Method: Ground
Country of Origin: