

Project:


Purolinear 360 LED Wall Bar

SKU: 23QSKN122R120PHA

A system of linear tubes, set within the geometry of surface-mounted cylinder brackets, rotate individually to direct the LED illumination in 360 degrees along their axis. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability.

For additional options and pricing, contact our Contract Sales Team at quotes@sonneman.com

Learn more: <https://sonnemanlight.com/purolinear-360-led-wall-bar>



Dimensions

Height	24.75"
Width	26.75"
Extends	2.75"
Minimum Extension	2.75"
Maximum Extension	2.75"
Shape	Single N
Size	24"

Electrical Specs

Bulb(s) Included?	Yes
Bulb 1 Type	Integral LED
Total LED, Bulb or Socket Count	3
Input Voltage	100-277VAC
Wattage	7
Initial Lumens	2070
Delivered Lumens	1470
Kelvin	3000K
CRI	90
Power Supply Type	Driver
Power Supply Quantity	1
Power Supply Location	Remote
Dimming Type	TRIAC/ELV/0-10V

Installation

Installation	Licensed electrician required
--------------	-------------------------------

Diffuser(s), Shade(s) and Lens(es)

Diffuser Type	Optical Acrylic
---------------	-----------------

General Listings

Color/Finish	Satin Black (.25)
Features	ADA Compliant, Damp Rated
Certification	C-ETL-US

Available Finishes

Available Finishes	Polished Chrome (.01), Satin Black (.25), Satin Chrome (.23), Satin White (.03)
--------------------	---

Available Color Temperatures

Available Color Temperatures	3000k
------------------------------	-------