WAC LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

60W/96W 120-277VAC INPUT 24VDC

Model & Product	L x W x H
❍ PS-24DC-U60R-BT Remote Enclosed Power Supply 100-277VAC Input 24VDC Output 60 Watt ❍ PS-24DC-U96R-BT Remote Enclosed Power Supply 100-277VAC Input 24VDC Output 96 Watt	7.4IN x 3.62IN x 1IN 8.66IN x 3.66IN x 1.6IN

Example: **PS-24DC-U60R-BT**

DESCRIPTION

This class 2 and class P, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring multiple low voltage fixtures. Class 2 power supplys are intrinsicallysafer power supplys because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Power supply hasknockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 power supplys do not require conduit sheathed cable or clamp wiring techniques. This power supplyhas a low minimum load requirement of 6W to allow the use of LED products. May be dimmed using a TRIAC or electronic low voltage dimmer.



FEATURES

- Short circuit, over current, over voltage, over temperature protection.
- Class 2 Output
- 6W minimum load; 60 maximum load for PS-24DC-U60R-BT
- 9.6W minimum load; 96 maximum load for PS-24DC-U60R-BT
- 5 year warranty

SPECIFICATIONS

Input:	100-277 VAC, 50/60Hz
Dimming:	ELV: %
Rated Life:	50000 Hours
Finish:	BLACK
Operating Temp:	-4°F to 104°F (-20°C to 60°C)
Standards:	UL, cUL, Damp Location Listed

FINISHES:



BLACK

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. June 2022

WAC LIGHTING

60W/96W 120-277VAC INPUT 24VDC

Fixture Type:

Catalog Number:

Project:

Location:

ACCESSORIES

Model	*Description*	*Finish*

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. June 2022